


Sockets

OPEN SPELTER WIRE ROPE SOCKETS

CLOSED SPELTER WIRE ROPE SOCKETS

* FORGED STEEL THROUGH 1-1/2"
 † ALLOY CAST STEEL 1-5/8" THRU 4".

**G-416
S-416**



* FORGED STEEL THROUGH 1-1/2"
 † ALLOY CAST STEEL 1-5/8" THRU 4".

**G-417
S-417**



Size (in.)	G-416 Stock No. Galv.	S-416 Stock No. S.C.	Weight Each (lbs.)
*1/4	1039619	1039628	1.10
*5/16-3/8	1039637	1039646	1.30
*7/16-1/2	1039655	1039664	2.25
*9/16-5/8	1039673	1039682	4.00
*3/4	1039691	1039708	5.83
*7/8	1039717	1039726	9.58
*1	1039735	1039744	15.50
*1 1/8	1039753	1039762	21.50
*1 1/4-1 3/8	1039771	1039780	31.00
*1 1/2	1039799	1039806	47.25
†1 5/8	1039815	1039824	53.88
†1 3/4-1 7/8	1039833	1039842	82.00
†2-2 1/8	1039851	1039860	125.00
†2 1/4-2 3/8	1039879	1039888	167.00
†2 1/2-2 5/8	1041633	1041642	252.00
†2 3/4-2 7/8	1041651	1041660	315.00
†3-3 1/8	1041679	1041688	380.00
†3 1/4-3 3/8	1041697	1041704	434.00
†3 1/2-3 5/8	1041713	1041722	563.00
†3 3/4-4	1041731	1041740	783.00

Size (in.)	G-417 Stock No. Galv.	S-417 Stock No. S.C.	Weight Each (lbs.)
*1/4	1039897	1039904	.50
*5/16-3/8	1039913	1039922	.75
*7/16-1/2	1039931	1039940	1.50
*9/16-5/8	1039959	1039968	2.50
*3/4	1039977	1039986	4.25
*7/8	1039995	1040000	7.25
*1	1040019	1040028	10.50
*1 1/8	1040037	1040046	14.25
*1 1/4-1 3/8	1040055	1040064	19.75
*1 1/2	1040073	1040082	29.20
†1 5/8	1040091	1040108	36.00
†1 3/4-1 7/8	1040117	1040126	57.25
†2-2 1/8	1040135	1040144	79.00
†2 1/4-2 3/8	1040153	1040162	105.00
†2 1/2-2 5/8	1041759	1041768	140.00
†2 3/4-2 7/8	1041777	11041786	220.00
†3-3 1/8	1041795	1041802	276.00
†3 1/4-3 3/8	1041811	1041820	313.00
†3 1/2-3 5/8	1041839	1041848	400.00
†3 3/4-4	1041857	1041866	542.00

**WIRELOCK®
SOCKETING COMPOUND**


W416-7

- 100% termination efficiency
- Temperature operating range: 65°F to +240°F
- Ideal for on-site applications
- No hazardous molten metal
- Improves fatigue life
- Pouring temperature without booster pack is 48° F to 110° F
- One booster pack pouring temperature is 35° F to 48° F
- Two Booster pack pouring temperature is 27° F to 35° F
- Refer to Wirelock® Technical Manual for more information.

NOTE: For use on 416 & 417 sockets only.



**S-421T
TERMINATOR™
(Complete)
Cast Steel**



**S-421TW
Wedge Only**

Rope Size	Stock No. Complete With Wedge and Pin S.C.	Stock No. Wedges S.C.	Weight Each Complete With Wedge and Pin (lbs.)
3/8	1035000	1035555	2.66
1/2	1035009	1035564	5.75
5/8	1035018	1035573	8.27
3/4	1035027	1035582	13.80
7/8	1035036	1035591	20.50
1	1035045	1035600	29.60
1 1/8	1035054	1035609	42.88
1 1/4	1040448	1040607	57.50

Kit Size	Kits Per Case	Stock No.	Weight Each (lbs.)
100cc	20	1039602	.62
250cc	12	1039604	1.25
500cc	12	1039606	2.54
1000cc	12	1039608	4.59
2000cc	6	1039610	9.00

**WIRELOCK
BOOSTER
PACKS**

Wirelock Kit Size	Stock No.
100cc	1039603
250cc	1039605
500cc	1039607
1000cc	1039609
2000cc	1039611