

Crosby® Forged Shackles

SCREW PIN




G-209 S-209

Screw pin anchor shackles meet the requirements of Federal Specification RR-C-271D Type IVA, Grade A, Class 2.

Load Rated

- Working Load Limit permanently shown on every shackle.
- Forged — Quenched and Tempered, with alloy pins.
- Capacities 1/3 thru 55 tons.
- Look for the red pin . . . the mark of genuine Crosby quality.
- Shackles can be furnished proof tested with certificates to designated standards, such as ABS, DNV, Lloyds, or other certification. Charges for proof testing and certification available when requested at the time of order.
- Hot Dip galvanized or Self Colored.
- Fatigue rated.



ROUND PIN




G-213 S-213

Round pin anchor shackles meet the requirements of Federal Specification RR-C-271D Type IVA, Grade A, Class 1.



Nominal Size (in.)	Working Load Limit* (tons)	Stock No.				Weight Each (lbs.)	
		G-209 Galv.	S-209 S.C.	G-213 Galv.	S-213 S.C.	G-209 S-209	G-213 S-213
3/16	† 1/3	1018357	—	—	—	.05	—
1/4	1/2	1018375	1018384	1018017	1018026	.12	.13
5/16	3/4	1018393	1018400	1018035	1018044	.19	.17
3/8	1	1018419	1018428	1018053	1018062	.31	.25
7/16	1 1/2	1018437	1018446	1018071	1018080	.38	.38
1/2	2	1018455	1018464	1018099	1018106	.63	.70
5/8	3 1/4	1018473	1018482	1018115	1018124	1.38	1.50
3/4	4 3/4	1018491	1018507	1018133	1018142	2.25	2.32
7/8	6 1/2	1018516	1018525	1018151	1018160	3.38	3.40
1	8 1/2	1018534	1018543	1018179	1018188	5.32	5.00
1 1/8	9 1/2	1018552	1018561	1018197	1018204	6.81	6.97
1 1/4	12	1018570	1018589	1018213	1018222	9.50	9.75
1 3/8	13 1/2	1018598	1018605	1018231	1018240	13.25	13.25
1 1/2	17	1018614	1018623	1018259	1018268	17.20	17.25
1 3/4	25	1018632	1018641	1018277	1018286	30.38	29.46
2	35	1018650	1018669	1018295	1018302	45.00	45.75
2 1/2	†55	1018678	1018687	—	—	85.75	—



Nominal Size (in.)	Working Load Limit* (tons)	Dimensions (in.)												Tolerance +/-	
		A	B	C	D	E	F	G	H	L	M	N	P	C	A
3/16	† 1/3	.38	.25	.88	.19	.60	.56	.98	1.47	.16	1.12	—	.19	.06	.06
1/4	1/2	.47	.31	1.13	.25	.78	.61	1.28	1.84	.19	1.38	1.34	.25	.06	.06
5/16	3/4	.53	.38	1.22	.31	.84	.75	1.47	2.09	.22	1.66	1.59	.31	.06	.06
3/8	1	.66	.44	1.44	.38	1.03	.91	1.78	2.49	.25	2.03	1.86	.38	.13	.06
7/16	1 1/2	.75	.50	1.69	.44	1.16	1.06	2.03	2.91	.31	2.38	2.13	.44	.13	.06
1/2	2	.81	.63	1.88	.50	1.31	1.19	2.31	3.28	.38	2.69	2.38	.50	.13	.06
5/8	3 1/4	1.06	.75	2.38	.63	1.69	1.50	2.94	4.19	.44	3.34	2.91	.69	.13	.06
3/4	4 3/4	1.25	.88	2.81	.75	2.00	1.81	3.50	4.97	.50	3.97	3.44	.81	.25	.06
7/8	6 1/2	1.44	1.00	3.31	.88	2.28	2.09	4.03	5.83	.50	4.50	3.81	.97	.25	.06
1	8 1/2	1.69	1.13	3.75	1.00	2.69	2.38	4.69	6.56	.56	5.07	4.53	1.06	.25	.06
1 1/8	9 1/2	1.81	1.25	4.25	1.16	2.91	2.69	5.16	7.47	.63	5.59	5.13	1.25	.25	.06
1 1/4	12	2.03	1.38	4.69	1.29	3.25	3.00	5.75	8.25	.69	6.16	5.50	1.38	.25	.06
1 3/8	13 1/2	2.25	1.50	5.25	1.42	3.63	3.31	6.38	9.16	.75	6.84	6.13	1.50	.25	.13
1 1/2	17	2.38	1.63	5.75	1.54	3.88	3.63	6.88	10.00	.81	7.35	6.50	1.62	.25	.13
1 3/4	25	2.88	2.00	7.00	1.84	5.00	4.19	8.86	12.34	1.00	9.08	7.75	2.25	.25	.13
2	35	3.25	2.25	7.75	2.08	5.75	4.81	9.97	13.68	1.22	10.34	8.75	2.40	.25	.13
2 1/2	†55	4.13	2.75	10.50	2.71	7.25	5.69	12.87	17.84	1.38	13.00	—	3.13	.25	.25